1	
(\mathbf{A})	-S

SAFETY DATA SHEET (SDS)

DUCTILE IRON/ COMPACTED GRAPHITE IRON (CGI) CASTINGS SDS SC-000-042 Rev. 12

© 2013 American Foundry Society

Meets the Requirements of OSHA Standard 29 CFR 1910.1200 Hazard Communication and EPA Supplier Notification Requirements under Section 313 of the Emergency Planning and Community Right-to-Know Act.

DATE ISSUED

10/13

SECTION 1—PRODUCT IDENTIFICATION & COMPANY INFORMATION

PRODUCT NAME

DUCTILE IRON and COMPACTED GRAPHITE IRON (CGI) CASTINGS

OTHER DESIGNATIONS: ASTM (American Society for Testing & Materials) Specification No's., (ACI (Alloy Casting Institute) Alloy Designations— Grades)

ASTM: A395, A536, A476, A874, A897, Compacted Graphite Iron (CGI) A842

PRODUCT IDENTIFICATION (Label Identifier)

MANUFACTURER'S NAME	STREET ADDRESS
EMERGENCY TELEPHONE NO.	MAILING ADDRESS
TELEPHONE NO.	CITY, STATE, ZIP CODE, COUNTRY
FAX NO.	E-MAIL ADDRESS/WEBSITE

RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

Solid casting; no restrictions

SECTION 2—HAZARD IDENTIFICATION

CLASSIFICATION

Castings are metallic articles that do not present hazards in their original form.

OTHER INFORMATION

- 1. Grinding castings that have not been cleaned or that contain embedded sand may generate significant amounts of dust containing crystalline silica.
- 2. Fumes from hot processes may contain other compounds with different exposure limits. Dust or fumes generated by machining, grinding, welding or thermal cutting of the casting may produce airborne contaminants. Consult Sections 3 & 8 for further information.

SECTION 3—COMPOSITION/INFORMATION ON INGREDIENTS			
CHEMICAL NAME/COMMON NAME/SYNONYM	Wt %	CAS NUMBER	
Carbon (C)	3.04.3	7440-44-0	
Chromium (Cr)	0.020.13	7440-47-3	
Copper (Cu)	0.01–1.5	7440-50-8	
Iron (Fe)	87.7–95.1	7439-89-6	
Magnesium (Mg)	0.00010.10	7439-95-4	
Manganese (Mn)	<1.2	7439-96-5	
Molybdenum (Mo)	0.010.50	7439-98-7	
Nickel (Ni)	0.1–-2	7440-02-0	
Silicon (Si)	1.8–4	7440-21-3	
Tin (Sn)	0.1–0.15	7440-31-5	

EYE CONTACT:		SECTION 4—FIRST AID	MEASURES	
	Not applicable	romonto		
SKIN CONTACT:	No special requi	rements		
INGESTION:	Not applicable			
INHALATION	Not applicable			
		ECTION 5—FIREFIGHTI	NG MEASURES	
FLAMMABLE PRO		Not applicable		
EXTINGUISHING		Not applicable		
PROTECTION OF FIREFIGHTERS: Not applicable				
	SECTION	ON 6—ACCIDENTAL RE	LEASE MEASURES	
Not applicable				
		SECTION 7—HANDLING	& STORAGE	
RECOMMENDED S	TORAGE			
No special requirer	ments			
PROCEDURES FOR	R HANDLING			
Proper hand and for	oot protection is rec	commended.		
	SECTION 8—I	EXPOSURE CONTROLS	PERSONAL PROTECTION	
ENGINEERING CO				
None Required. Th	here are no health h	nazards from castings in s		
	SUBSTANC		ACGIH TLV mg/m ³	OSHA PEL mg/m ³
Carbon (C)	SUBSTANC		ACGIH TLV	
. ,	SUBSTANC		ACGIH TLV mg/m ³	mg/m ³
Chromium (Cr)	SUBSTANC		ACGIH TLV mg/m ³ N/E	mg/m ³ N/E
Carbon (C) Chromium (Cr) Copper (Cu) Iron (Fe)	SUBSTANC		ACGIH TLV mg/m ³ N/E 0.5	mg/m ³ N/E 1
Chromium (Cr) Copper (Cu)			ACGIH TLV mg/m ³ N/E 0.5 1	mg/m ³ N/E 1 1
Chromium (Cr) Copper (Cu) Iron (Fe) Magnesium (Mg) oxi			ACGIH TLV mg/m ³ N/E 0.5 1 N/E	<u>mg/m³</u> N/E 1 1 N/E
Chromium (Cr) Copper (Cu) Iron (Fe) Magnesium (Mg) oxi Manganese (Mn)	ide		ACGIH TLV mg/m ³ N/E 0.5 1 N/E 10 (I)	mg/m ³ N/E 1 1 N/E 15
Chromium (Cr) Copper (Cu) Iron (Fe)	ide		ACGIH TLV mg/m ³ N/E 0.5 1 N/E 10 (I) 0.02 (R); 0.1 (I)	mg/m ³ N/E 1 1 N/E 15 5 (C)
Chromium (Cr) Copper (Cu) Iron (Fe) Magnesium (Mg) oxi Manganese (Mn) Molybdenum (Mo) in	ide		ACGIH TLV mg/m ³ N/E 0.5 1 N/E 10 (I) 0.02 (R); 0.1 (I) 10 (I); 3 (R)	mg/m ³ N/E 1 1 N/E 15 5 (C) 15
Chromium (Cr) Copper (Cu) Iron (Fe) Magnesium (Mg) oxi Manganese (Mn) Molybdenum (Mo) in Nickel (Ni) Silicon (Si) Total dust	ide		ACGIH TLV mg/m ³ N/E 0.5 1 N/E 10 (I) 0.02 (R); 0.1 (I) 10 (I); 3 (R) 1.5 (I) N/E	mg/m ³ N/E 1 N/E 15 5 (C) 15 1 15
Chromium (Cr) Copper (Cu) Iron (Fe) Magnesium (Mg) oxi Manganese (Mn) Molybdenum (Mo) in Nickel (Ni) Silicon (Si)	ide		ACGIH TLV mg/m ³ N/E 0.5 1 N/E 10 (I) 0.02 (R); 0.1 (I) 10 (I); 3 (R) 1.5 (I)	mg/m ³ N/E 1 1 N/E 15 5 (C) 15 1

SUPPLEMENTAL INFORMATION

Grinding castings that have not been cleaned or that contain embedded sand may generate significant amounts of dust containing crystalline silica.

Fumes from hot processes may contain other compounds with different exposure limits than those listed above. Dust or fumes generated by machining, grinding, welding or thermal cutting of the casting may produce airborne contaminants. Exposure limits for the most common contaminants are offered as reference. Please consult a competent person for guidance on exposure assessment and controls.

In particular, Hexavalent Chromium is an OSHA Expanded Health Standard; refer to OSHA 29 CFR 1910.1026- Chromium (VI) for complete requirements.

SUBSTANCE	ACGIH TLV mg/m ³	OSHA PEL mg/m ³
Chromium Compounds (as Cr)		
Chromium (II) inorganic compounds	N/E	0.5
Chromium (III) inorganic compounds	0.5	0.5
Chromium (VI) inorganic compounds, certain water in	soluble 0.01	0.005
Chromium (VI) inorganic compounds, water soluble	0.05	0.005
Chromium (VI) all forms and compounds	N/E	0.005
Copper Compounds (as Cu)		
Fume, as Cu	0.2	0.1
Dusts and mists, as Cu	1	1
Iron Compounds		
Iron oxide (Fe_2O_3) fume	N/E	10
Iron oxide (Fe ₂ O ₃)	5 (R)	N/E
Nickel Compounds (as Ni)		
Insoluble, inorganic compounds	0.2(I)	1
Soluble, inorganic compounds	0.1(I)	1
Nickel oxide	0.2(I)	1
Tin compounds (as Sn)		
Tin Oxide & inorganic compounds, except SnH ₄	2	N/E
Inorganic compounds, except oxides, as Sn	N/E	2
Tin Oxides, as Sn	2.0	N/E
R = Respirable fraction	o of Industrial Hygiopists (ACCIH)	
TLV =Threshold Limit Value/American ConferencePEL =Permissible Exposure Limit / OSHAmg/m³ =milligrams per cubic meterPERSONAL PROTECTIONProper hand and foot protection is recommended.		
TLV =Threshold Limit Value/American ConferencePEL =Permissible Exposure Limit / OSHAmg/m³ =milligrams per cubic meterPERSONAL PROTECTIONProper hand and foot protection is recommended.	e of Industrial Hygienists (ACGIH)	
TLV = Threshold Limit Value/American Conference PEL = Permissible Exposure Limit / OSHA mg/m ³ = milligrams per cubic meter PERSONAL PROTECTION Proper hand and foot protection is recommended. SECTION 9—PHYSICA		
TLV = Threshold Limit Value/American Conference PEL = Permissible Exposure Limit / OSHA mg/m³ = milligrams per cubic meter PERSONAL PROTECTION Proper hand and foot protection is recommended. SECTION 9—PHYSICA APPEARANCE /PHYSICAL STATE		
TLV = Threshold Limit Value/American Conference PEL = Permissible Exposure Limit / OSHA mg/m³ = milligrams per cubic meter PERSONAL PROTECTION Proper hand and foot protection is recommended. SECTION 9—PHYSICA APPEARANCE /PHYSICAL STATE Solid, silver gray in color	L & CHEMICAL PROPERTIES	
TLV = Threshold Limit Value/American Conference PEL = Permissible Exposure Limit / OSHA mg/m ³ = milligrams per cubic meter PERSONAL PROTECTION Proper hand and foot protection is recommended. Section 9—PHYSICA Section 9—PHYSICA APPEARANCE /PHYSICAL STATE Solid, silver gray in color ODOR/ODOR THRESHOLD Section 1000	L & CHEMICAL PROPERTIES VAPOR DENSITY Not applicable SPECIFIC GRAVITY (relative de	nsity)
TLV = Threshold Limit Value/American Conference PEL = Permissible Exposure Limit / OSHA mg/m³ = milligrams per cubic meter PERSONAL PROTECTION Proper hand and foot protection is recommended. SECTION 9—PHYSICA APPEARANCE /PHYSICAL STATE Solid, silver gray in color ODOR/ODOR THRESHOLD None	L & CHEMICAL PROPERTIES VAPOR DENSITY Not applicable	nsity)
TLV = Threshold Limit Value/American Conference PEL = Permissible Exposure Limit / OSHA mg/m³ = milligrams per cubic meter PERSONAL PROTECTION Proper hand and foot protection is recommended. Section 9—PHYSICA Section 9—PHYSICA APPEARANCE /PHYSICAL STATE Solid, silver gray in color ODOR/ODOR THRESHOLD None MELTING POINT/FREEZING POINT	L & CHEMICAL PROPERTIES VAPOR DENSITY Not applicable SPECIFIC GRAVITY (relative de	nsity)
TLV = Threshold Limit Value/American Conference PEL = Permissible Exposure Limit / OSHA mg/m³ = milligrams per cubic meter PERSONAL PROTECTION Proper hand and foot protection is recommended. Section 9—PHYSICA Section 9—PHYSICA APPEARANCE /PHYSICAL STATE Solid, silver gray in color ODOR/ODOR THRESHOLD None MELTING POINT/FREEZING POINT Approximately 2350°F (1300°C)	L & CHEMICAL PROPERTIES VAPOR DENSITY Not applicable SPECIFIC GRAVITY (relative de 7.85 g/cm ³ for iron	nsity)
TLV = Threshold Limit Value/American Conference PEL = Permissible Exposure Limit / OSHA mg/m³ = milligrams per cubic meter PERSONAL PROTECTION Proper hand and foot protection is recommended. Section 9—PHYSICA APPEARANCE /PHYSICAL STATE Solid, silver gray in color ODOR/ODOR THRESHOLD None MELTING POINT/FREEZING POINT Approximately 2350°F (1300°C) BOILING POINT	L & CHEMICAL PROPERTIES VAPOR DENSITY Not applicable SPECIFIC GRAVITY (relative de 7.85 g/cm ³ for iron VAPOR PRESSURE	nsity)
TLV = Threshold Limit Value/American Conference PEL = Permissible Exposure Limit / OSHA mg/m³ = milligrams per cubic meter PERSONAL PROTECTION Proper hand and foot protection is recommended. Section 9—PHYSICA APPEARANCE /PHYSICAL STATE Solid, silver gray in color ODOR/ODOR THRESHOLD None MELTING POINT/FREEZING POINT Approximately 2350°F (1300°C) BOILING POINT 5000°F (2750°C) for iron	L & CHEMICAL PROPERTIES VAPOR DENSITY Not applicable SPECIFIC GRAVITY (relative de 7.85 g/cm ³ for iron VAPOR PRESSURE Not applicable	nsity)
TLV = Threshold Limit Value/American Conference PEL = Permissible Exposure Limit / OSHA mg/m³ = milligrams per cubic meter PERSONAL PROTECTION Proper hand and foot protection is recommended. Section 9—PHYSICA APPEARANCE /PHYSICAL STATE Solid, silver gray in color ODOR/ODOR THRESHOLD None MELTING POINT/FREEZING POINT Approximately 2350°F (1300°C) BOILING POINT 5000°F (2750°C) for iron FLASH POINT	L & CHEMICAL PROPERTIES VAPOR DENSITY Not applicable SPECIFIC GRAVITY (relative de 7.85 g/cm ³ for iron VAPOR PRESSURE Not applicable EVAPORATION RATE	nsity)
TLV = Threshold Limit Value/American Conference PEL = Permissible Exposure Limit / OSHA mg/m ³ = milligrams per cubic meter PERSONAL PROTECTION Proper hand and foot protection is recommended. Section 9—PHYSICA Section 9—PHYSICA APPEARANCE /PHYSICAL STATE Solid, silver gray in color ODOR/ODOR THRESHOLD None MELTING POINT/FREEZING POINT Approximately 2350°F (1300°C) BOILING POINT 5000°F (2750°C) for iron FLASH POINT Not applicable for solid castings	L & CHEMICAL PROPERTIES VAPOR DENSITY Not applicable SPECIFIC GRAVITY (relative de 7.85 g/cm ³ for iron VAPOR PRESSURE Not applicable EVAPORATION RATE Not applicable	nsity)
TLV = Threshold Limit Value/American Conference PEL = Permissible Exposure Limit / OSHA mg/m³ = milligrams per cubic meter PERSONAL PROTECTION Proper hand and foot protection is recommended. Section 9—PHYSICA Section 9—PHYSICA APPEARANCE /PHYSICAL STATE Solid, silver gray in color ODOR/ODOR THRESHOLD None MELTING POINT/FREEZING POINT Approximately 2350°F (1300°C) BOILING POINT 5000°F (2750°C) for iron FLASH POINT Not applicable for solid castings FLAMMABILITY Solid castings	L & CHEMICAL PROPERTIES VAPOR DENSITY Not applicable SPECIFIC GRAVITY (relative de 7.85 g/cm ³ for iron VAPOR PRESSURE Not applicable EVAPOR ATION RATE Not applicable SOLUBILITY IN WATER	nsity)
TLV = Threshold Limit Value/American Conference PEL = Permissible Exposure Limit / OSHA mg/m ³ = milligrams per cubic meter PERSONAL PROTECTION Proper hand and foot protection is recommended. Section 9—PHYSICA Section 9—PHYSICA APPEARANCE /PHYSICAL STATE Solid, silver gray in color ODOR/ODOR THRESHOLD None MELTING POINT/FREEZING POINT Approximately 2350°F (1300°C) BOILING POINT 5000°F (2750°C) for iron FLASH POINT Not applicable for solid castings FLAMMABILITY Not flammable	L & CHEMICAL PROPERTIES VAPOR DENSITY Not applicable SPECIFIC GRAVITY (relative de 7.85 g/cm ³ for iron VAPOR PRESSURE Not applicable EVAPORATION RATE Not applicable SOLUBILITY IN WATER Insoluble	ensity)
TLV = Threshold Limit Value/American Conference PEL = Permissible Exposure Limit / OSHA mg/m ³ = milligrams per cubic meter PERSONAL PROTECTION Proper hand and foot protection is recommended. Section 9—PHYSICA Section 9—PHYSICA APPEARANCE /PHYSICAL STATE Solid, silver gray in color ODOR/ODOR THRESHOLD None MELTING POINT/FREEZING POINT Approximately 2350°F (1300°C) BOILING POINT 5000°F (2750°C) for iron FLASH POINT Not applicable for solid castings FLAMMABILITY Not flammable UPPER AND LOWER FLAMMABILITY LIMITS	L & CHEMICAL PROPERTIES VAPOR DENSITY Not applicable SPECIFIC GRAVITY (relative de 7.85 g/cm ³ for iron VAPOR PRESSURE Not applicable EVAPORATION RATE Not applicable SOLUBILITY IN WATER Insoluble pH	nsity)

DECOMPOSITION TEMPERATURE	ECOMPOSITION TEMPERATURE		PARTITION COEFFICIENT		
Not applicable Not applicable					
SECTION 10—STABILITY & REACTIVITY			ITY		
CHEMICAL STABILITY					
Stable					
CONDITIONS TO AVOID					
REACTIVITY INCOMPATIBLE MATERIALS			IATERIALS		
Not reactive None HAZAPDOUS DECOMPOSITION PRODUCTS POSSIBILITY OF HAZAPDOUS PEACTIONS			AZARDOUS REACTIONS		
HAZARDOUS DECOMPOSITION PRODUCTS POSSIBILITY OF HAZARDOUS REACTIONS None Not applicable					
SECTION 11—T	OXICOL			ATION	
POTENTIAL HEALTH EFFECTS	ONICOL				
EYE CONTACT: None					
SKIN: None					
INGESTION: None					
INHALATION: None					
Carcinogen	Classifi	cation of	Ingredie	nts	
INGREDIENT	OSHA	NTP	IARC	TARGET ORGAN	
Nickel (metal)	NL	R	2B	Lung, Nose	
 NTP—National Toxicology Program K = Known to be a Human Carcinogen R = Reasonably Anticipated to be a Human Carcinogen (RAHC) IARC—International Agency for Research on Cancer 1 = Carcinogen to Humans 2A = Probably Carcinogenic to Humans 2B = Possibly Carcinogenic to Humans 3 = Unclassifiable as to Carcinogenicity in Humans 4 = Probably not Carcinogenic to Humans 					
Other NL = Not Listed					
SECTION 12—ECOLOGICAL INFORMATION					
ECOTOXICITY		PERSIS		ND DEGRADABILITY	
Not applicable		Not applicable			
BIOACCUMULATION POTENTIAL		MOBILITY IN SOIL			
Not applicable		Not applicable			
OTHER ADVERSE EFFECTS					
Not applicable					
SECTION 13—	DISPOS	SAL CON	SIDERAT	IONS	
Recover or recycle if possible. Dispose of accord machining, welding, etc. may be classified as a h					
SECTION 14—TRANSPORT INFORMATION					
US DEPARTMENT OF TRANSPORTATION CANADIAN TRANSPORTATION OF DANGEROUS			SPORTATION OF DANGEROUS		
(DOT)-HMR (Hazardous Materials Registration)	(GOODS (TDG)			
Not Regulated Not regulated					
UN SHIPPING NAME					

TRANSPORT HAZARD CLASS	PACKING GROUP	
Not regulated	Not regulated	
ENVIRONMENTAL HAZARDS	LABEL(S) REQUIRED?	
None	No	
TRANSPORT IN BULK	SPECIAL SHIPPING INFORMATION	
Not applicable	Not applicable	
SECTION 15—REGU	ILATORY INFORMATION	
US-OSHA (Hazard Communication Standard)		
US-EPA (Toxic Substances Control Act-TSCA)		
All components of these products are on the TSCA in	ventory list or are excluded from listing.	
US-EPA (SARA Title III)		
	Manganese and Nickel , may be subject to reporting under and Reauthorization Act of 1986 and 40 CFR Part 72.	
CANADA-WHMIS (Workplace Hazardous Materials In	formation System)	
This SDS has been prepared according to the hazard SDS contains the information required by the CPR.	criteria of the Controlled Product Regulations (CPR) and the	
CANADA DSL (Domestic Substances List) Inventory	Status	
All components of these products are on the DSL Inve	entory.	
CEPA (Canadian Environmental Protection Act)		
Chromium and Nickel are on the CEPA Priorities Sub	stances Lists	
EINECS No. (European Inventory of Existing Comme	rcial Chemical Substances)	
All components of these products are on the EINECS	list.	
RoHS (Restriction of Certain Hazardous Substances)	Compliance	
Castings comply with RoHS		
CALIFORNIA PROPOSITION 65 Compliance		
WARNING: This product contains or produces chemic birth defects (or other reproductive harm). (California	cals known to the State of California to cause cancer and Health & Safety Code 25248.5 et seq.)	
US STATE REGULATORY INFORMATION		
Some of the components listed in Section 3 may be c	overed under specific state regulations.	
SECTION 16 — O	THER INFORMATION	
SDS SHEET PREPARED BY	DATE	
American Foundry Society, Inc.	10/13	
Occupational Safety & Health Committee (10-Q)		

procedures are believed to be generally applicable. However, each user should review the recommendations in specific context of the intended use and determine if they are appropriate.

PRODUCT IDENTIFIER

SC-000-042 Rev. 12

DUCTILE IRON/COMPACTED GRAPHITE IRON (CGI) CASTINGS

SUPPLIER IDENTIFICATION	HAZARD PICTOGRAMS
Company Name	None*
Street Address	SIGNAL WORD
Mailing Address	None*
City State	
Zip/Postal Code Country	
Emergency Phone Number	
Other Info	
PRECAUTIONARY STATEMENTS	HAZARD STATEMENTS
None*	None*

*Castings do not present hazards in their original form.

OTHER INFORMATION

- 1. Grinding castings that have not been cleaned or that contain embedded sand may generate significant amounts of dust containing crystalline silica.
- 2. Fumes from hot processes may contain other compounds with different exposure limits. Dust or fumes generated by machining, grinding, welding or thermal cutting of the casting may produce airborne contaminants. Consult Sections 3 & 8 of the SDS for further information.